

Section 1. Product and Company Identification

Product Name	PRECIDIUM™ LS1150D FR2 Resin (Black)
Manufacturer	Quantum Technical Services Ltd. (Db a Quantum Chemical) 15 Riel Drive St. Albert, AB, Canada T8N 3Z2 Tel: (780) 458-3355 (non-emergency phone number) Fax: (780) 458-2852 www.quantumchemical.com
Chemical Emergencies	For 24-Hour Emergency call Canutec at 613.996.6666

Section 2. Hazards Identification

2.1 Label Elements:

Pictogram:



Signal Word:	Warning
Hazard Statements:	H317 May cause an allergic skin reaction. H412 Harmful to aquatic life with long lasting effects.
Precautionary Statements:	P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/protective clothing/eye protection/face protection.
Response:	P370+P378 In case of fire, use carbon dioxide, dry chemical, or foam to extinguish. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P332+P313 If skin irritation occurs: Get medical advice/attention. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P301+P311+P331 IF SWALLOWED: Call a POISON CENTER/doctor. Do NOT induce vomiting. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention.
Storage:	P403+P233 Store in a well-ventilated place. Keep container tightly closed. P235 Keep cool.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Section 3. Composition and Ingredient Information

Hazardous Ingredients:	%	T.L.V.	C.A.S. #	OSHA PEL
Aspartic Ester	>40	N/D	Proprietary	N/D
Aspartic Ester	>10	N/D	Proprietary	N/D
Aldamine	> 5	N/D	54914-37-3	N/D
2-(2H-Benzotriazol-2-YL) -4,6—Di-Tert-Pentylphenol.	>1	N/D	25973-55-1	N/D
Ammonium Polyphosphate	>15	N/D	68333-79-9	N/D
Carbon Black	0-4	N/D	1333-86-4	See Section 11

Section 4. First Aid Measures

Eye Contact:	Immediately flush with plenty of water for at least 15 minutes, keeping eyelids open. If redness, itching, or a burning sensation develop, seek medical attention.
Skin Contact:	If skin is damaged or wounded, treat with saturated gauze pads or compresses using a freshly made up ascorbic acid solution (10g in 100g of water). Immediately flush skin with plenty of soap and water. Remove contaminated clothing and wash clothing before reuse.
Inhalation:	Move victim to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen and seek medical attention.
Ingestion:	Do not induce vomiting. Seek medical attention immediately.

Section 5. Fire Fighting Measures

Flash Point:	>200° F/(94°C).
Auto Ignition Temperature (C):	Not applicable.
Extinguishing Media:	Foam/carbon dioxide/dry chemical.
Protective Equipment:	Safety glasses and gloves.
Unusual Hazards:	During a fire, irritating and toxic gases and aerosols may be generated by thermal decomposition and combustion. Symptoms may not be immediately apparent. Obtain medical attention. Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.
Special Fire Fighting Procedures:	Firefighters should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme heat.
Sensitivity to Mechanical Impact:	Not available.
Sensitivity to Static Discharge:	Take precautionary measures against static discharge.

Section 6. Accidental Release Measures

Leak/Spill: Evacuate all non-essential personnel. Eliminate all sources of ignition. Ventilate area. Utilize recommended protective clothing. Dike area to prevent spreading. Absorb with inert material. Collect material in open containers. Remove containers to a safe place and cover loosely.

Section 7. Handling and Storage

Handling Procedures: Do not breathe vapors or spray mist. Avoid contact with skin or eyes. Use only with adequate ventilation and personal protection. Remove contaminated personal protective equipment then wash hands and face thoroughly after handling, before eating or drinking. Keep container closed when not in use. Empty containers retain product residue and can be hazardous. Do not ingest. Avoid release to environment

Storage Needs: Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of reach of children.

Section 8. Exposure Controls and Personal Protection

Protective Equipment:

Eye/Type: Chemical tight goggles; full face shield if possibility of splashing.

Respiratory/Type: Respiratory masks should be worn at all times in the case of inadequate ventilation. A NIOSH/MSHA respirator is acceptable.

Gloves/Type: Use neoprene or rubber gloves.

Clothing/Type: Wear adequate protective coveralls and footwear.

Other/Type: Eyewash fountain. Emergency shower should be in close proximity.

Ventilation Requirements: Ventilate adequately. See complete details above under handling instructions.

Established exposure limits for carbon black are for respirable or inhalable dust. As all carbon black content in this product is fully dispersed in liquid, in our opinion these established exposure limits are not relevant.

Section 9. Physical and Chemical Properties

Physical State: Liquid.

Appearance: Black or tinted other select colors. Contact the manufacturer for details.

Odor: Slight.

Specific Gravity: N/D.

Vapor Pressure (mm Hg): 0.000014 MMHG. @ 20°C.

Vapor Density (Air=1): N/A.

Evaporation Rate: N/A.

Boiling Point: N/A.

pH: N/A.

Solubility in Water: Insoluble in water @ 68° F (20°C).

Freezing Point (°C): N/A.

Melting Point: N/A.

Percent Solids by Weight: 100%.

Percent Volatile (g/L): 0% by weight; 0% by volume.

VOC (g/l): 0% with water; 0% without water.

Viscosity: N/A.

Section 10. Stability and Reactivity

Stability:	Stable.
Conditions to Avoid:	Excessive heat, open flame, sparks, and strong oxidizing agents. Protect from atmospheric moisture.
Incompatibility:	Oxidizing agents/acids.
Reactivity Conditions:	Product is stable; hazardous polymerization will not occur.
Hazardous Products of Decomposition:	By fire: carbon monoxide, carbon dioxide. Nitrogen oxides. amines. ammonia, aliphatic fragments.
Conditions to Avoid:	Avoid incompatible reactants, especially strong bases, water or temperatures over 160°C.

Section 11. Toxicological Information

Acute Oral Toxicity (LD50):	>2000 mg/Kg (rats).
Irritancy of Material:	Slight to moderate.
Sensitizing Capability of Material:	May cause sensitization by skin contact.
Carcinogenicity of Material:	Negative; see note for Carbon Black.
Teratogenicity:	N/A.
Mutagenicity:	Negative.
Reproductive Effects:	N/A.
Carcinogenicity of Carbon Black:	In 2006 IARC (International Agency for Research on Cancer) re-affirmed its 1995 classification of carbon black as Group 2B (possibly carcinogenic to humans). All testing done to reach this conclusion were based on inhalation studies of carbon black in its powder form. In this product all carbon black is dispersed in liquid and there is no danger of inhalation.

Section 12. Ecological Information

Ecological Information:	Fish Toxicity (1) LC50: 66 MG/L.	Testing Time (1) 96 H.	Test Species (1) Brachydanio Rerio.
Biodegradability:	13%. Not readily biodegradable in a waste water treatment system.		

Section 13. Disposal Considerations

Waste Disposal:	Spilled material and water rinses are classified as chemical waste and must be disposed of in accordance with current local, municipal, provincial and federal regulations. Do not heat or cut empty containers with electric or gas torch.
-----------------	---

Section 14. Transport Information

Proper Shipping Name: Polyaspartic Polyurea.

Hazard Class: Non-regulated.

Section 15. Regulatory Information

TSCA

(Toxic Substance Control Act): If exported to the United States all chemical substances in this shipment comply with all applicable rules or orders under TSCA and there are no chemical substances in violation of TSCA or any applicable rule or order thereunder.

Section 16. Other Information

Revision Date: February 28, 2023

Note: This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Quantum Technical Services Ltd. The data on this sheet relates only to the specific material designated herein. Quantum Technical Services Ltd. assumes no legal responsibility for use or reliance upon this data.